ELECTRONIC SOMATIC CELL COUNT

Foss 250/300/360/400

(Unless otherwise stated all tolerances ±5%)

1.	Laboratory Requirements (see CP, item 33 & 34)			
	a.		preserved samples may be run up to 72 hours er initial collection	
	b.	if	ples may be run up to 7 days after initial collection preserved with 0.02% 2-bromo-2-nitropropane-1,3-diol conopol or 0.05% potassium dichromate $(K_2Cr_2O_7)$	
	c.	. Comparative test with DMSCC		
		1.	Performed by each analyst performing ESCC test _	
		2.	Test 4 samples (100K-200K, 300K-500K, 600K-800K and 900K-1.2M) in triplicate for both DMSCC (three separate smears each) and ESCC (three separate sub-samples each, do not read same sample three times)	
		3.	Results must be shown to be acceptable prior to official testing by analyst performing comparison, i.e. analyst is not certified until found acceptable. (co-requisite for certification)	
		4.	Copy of comparison and results in QC record (or easily accessible file in laboratory)	
	d.	Ana	lysts certified in DMSCC	
			APPARATUS	
2.	See	Cul	tural Procedures, items 1-5	
3.	Automated Electronic Somatic Cell Counters			
	a.	Fos	somatic 250	
	a.	Fos	somatic 300	
	b.	Fos	somatic 360	
	c.	Fos	somatic 400	
4.	Wate	er B	sath	
	a.	Cir	culating and thermostatically controlled to 37-42C	

REAGENTS

5.	. Stock Dye/Buffer Solution			
	a.	Dissolve 2.5g (or number of tablets specified by manufacturer) ethidium bromide $(C_{21}H_{20}BrN_3)$ in 1 liter deionized (DI) or MS water (caution TOXIC, use gloves when handling and do not breath dust), heat to 40-60C and mix to dissolve _		
	b.	Add 400g tripotassium citrate monohydrate $(C_6H_5O_7K_3 \not H_2O)$, 14.5g citric acid monohydrate $(C_6H_8O_7 \not H_2O)$, and 4 liters DI or MS water, heat to 40-60C and mix to dissolve		
	c.	Add dye and buffer solutions together and mix		
	d.	Add 50 mL neutral detergent, Triton X-100 to mixture and stir until dissolved		
	e.	Store refrigerated (0-4.4C) in airtight, light-proof container for no longer than 90 days		
	f.	Date prep Exp. Date		
6.	Sto	ck Detergent Solution		
	a.	Dissolve 10 mL neutral detergent, Triton X-100 in 1 liter of DI or MS water and heat 40-60C to complete solution		
	b.	Store refrigerated (0-4.4C) in airtight, container for no longer than 30 days		
	c.	Date prep Exp. Date		
7.	Amm	onium Hydroxide (NH $_4$ OH) Solution, Reagent Grade, 25% _		
8.		stock dye/buffer and detergent solutions labeled with e prepared and expiration date		
WORKING SOLUTIONS				
9.	Dye	/Buffer Solution		
	a.	Dilute 1 L dye/buffer stock solution (item 5) with 9 L DI or MS water		
	b.	Protect from light and use within 21 days		
	c.	Date prep Exp. Date		
10.	Rin	sing Solution (use within 7 days)		
	a.	Add 10 mL of stock neutral detergent stock solution (item 6) and 25 mL of ammonium hydroxide solution (item 7) and suspend to 10 L with DI or MS water		
	b.	Date prep Exp. Date		
(FO	FOSS250-2-Rev. 6/05)			

11.			lly, use manufacturer's reagent kits and instructions c for each instrument	
12.			king dye/buffer and rinsing solutions labeled with epared and expiration date	
			START UP	
13.	Cell Counter			
	a.	Check that the amount of dye/buffer solution (item 9) and rinsing (cleaning) solution (item 10) in instrument supply containers is of sufficient volume for the number of samples to be run		
	b.	Solutions not used beyond expiration date(s)		
	C.	Tur	n on power and cycle at least six times	
	d.	Perform a zero check before starting any measurements, within acceptable limits, single counts up to 5 and mean up to 3		
	e.		ANY ABOVE PARAMETERS ARE WRONG, CORRECT BEFORE CEEDING	
	f.		ords maintained on all parameters each time trument is used	
14.	Milk Standards			
	a.	Com	mercially prepared: # Date Rcd	
		1.	Four standards in ranges 100K-200K, 300K-500K, 600K-800K and 900K-1.2M	
		2.	Do DMSCC in triplicate on each standard in set and average counts, records maintained	
		3.	DMSCC check performed in rotation by all certified analysts	
		4.	Standards used within one week	
	b.	Certified provider: Lot# Exp. Date Date Rcd		
		1.	Four standards in ranges 100K-200K, 300K-500K, 600K-800K and 900K-1.2M	
		2.	Maintain copies of all provided DMSCC values	
		3.	Measure and maintain records of temperature (0-7.2C) of standards as received	

		4.	Maintain copies of all correspondence regarding problems	
		5.	Standards used by manufacturer's expiration date	
	C.	Lab	oratory prepared (weekly)	
		1.	Prepare from raw milk > 18 hours old preserved with 0.05% potassium dichromate $(K_2Cr_2O_7)$	
		2.	Or, preserved with 0.02% 2-bromo-2-nitropropane- 1,3-diol (Bronopol™)	
		3.	Standards <u>cannot</u> be preserved with formalin	
		4.	Prepare 4 standards in ranges 100K-200K, 300K-500K, 600K-800K and 900K-1.2M, used within one week Date prep Exp. Date	
		5.	Do DMSCC in triplicate on each standard and average counts, records maintained	
		6.	DMSCC check performed in rotation by all certified analysts	
	d.	Hou	rly Control Sample (instrument drift check)	
		1.	Use one of the standards (items 14a or b) in the 500-800K range, run in triplicate and determine average	
		2.	Optionally, prepare sufficient control/sample 500-800K range, run in triplicate and determine average	
			PROCEDURE	
15.	Test	ting	Standards (each time instrument used)	
	a.	and	t standards to 37-42C (using a temperature control) read within 30 minutes of reaching temperature, d once and then discarded, i.e. do not re-use	
	b.		by inverting at least 2x, place in rack and put o automatic track, run within 10 minutes	
	c.		the standards six times and average the counts for hevel, records maintained	
	d.	DMS	h standard's average must be within 10% of the CC (item 14) for that level, except within 15% 100K-200K standard, records maintained	
	e.	mus les	eatability - a standard in the 300K to 800K range t have a coefficient of variation (C_v) of 5% or s on 10 replicates (Refer to Operating Manual), ords maintained	

	f.	THESE PARAMETERS MUST BE ACHIEVED BEFORE PROCEEDING			
16.	Test	ting Samples			
	a.	Heat samples to 37-42C (using a temperature control) and read within 30 minutes of reaching temperature; samples <u>must not</u> be re-used and must be discarded after use			
	b.	Mix by inverting at least 2x, place in rack and put onto automatic track, run within 10 minutes of reaching the testing temperature			
17.	With continuous operation:				
	a.	Run a standard or optionally a control/sample (item 14d) in the 500K to 800K range hourly, must be within 5% of the original established instrument average value (optionally, within 10% of original DMSCC average)			
	b.	Run control 6x			
	c.	Run zero control (item 13d)			
	d.	Maintain records			
18.	Routine maintenance				
	a.	Perform as described in operating manual			
	b.	Maintain records			
		REPORTS			
19.	Comp	outing and Reporting Counts			
	a.	Count obtained x 1000 is the cell count/mL milk			
	b.	In reporting electronic somatic cell counts (ESCC/mL), record only first two left hand digits, raising second digit to next higher number when third digit is 6 or more			
	c.	Report the two left hand digits (rounded)			
		1. If the third digit is 5 the second digit is rounded by the following rule			
		a. When the second digit is odd round up, raise the second digit by 1 (odd up, 235 to 240)			
		 When the second digit is even round down, delete the 5 and report the second digit as is (even down, 225 to 220) 			
	d.	If count on instrument is < 100 report as < 100,000 ESCC/mL			